

A collection of Suprema biometric security devices, including smartphones, feature phones, and rugged handhelds, arranged on a white surface with a pink and white geometric overlay. The devices display various interfaces, including time, date, and biometric sensors.

Suprema Product Overview 2021

suprema
SECURITY & BIOMETRICS

Contents

BioStar 2
Access Control

Biometrics

Mobile

RFID
Reader

Controller

Contactless
Solution

System
Topology

Development
Tools

Product
Data Sheet





Proven Leader in Access Control, Time & Attendance and Biometric Solutions





Founded in 2000, Suprema Inc. has become a leading global provider of security and biometrics. By combining world-renowned biometric algorithms with superior engineering, Suprema has introduced a number of technology innovations to the security industry over the last two decades.

Suprema's extensive portfolio includes biometric access control systems, time & attendance solutions, fingerprint live scanners, mobile authentication solutions and embedded fingerprint modules.

The company has established itself as a global premium brand in the physical security industry and has worldwide sales network in over 140 countries. Suprema has no. 1 market share in biometric access control in Europe, Middle East and Africa region and has been named the world's top 50 security manufacturers for ten consecutive years.



Year Established

2000



Security Manufacturer

Top 50

(A&S Magazine, 2011-2020,
10 years in a row)



EMEA Market Share

No.1

in Biometric Access Control
(IHS Markit)



Number of people using
Suprema technologies

1 Billion +



Systems
in Operation

1.5 Million +

(worldwide installations)



Global Sales
Network in

140 Countries



National Identification
Projects in

23 Countries



Industry Patents and
Intellectual Properties

100+




Excellent Financial
Stability

A+

(Korea Investors Service)







BioStar 2 Access Control

BioStar 2 is a web-based, open, and integrated security platform that provides comprehensive functionality for access control, time & attendance, visitor management, and video logs. It supports web API to integrate BioStar 2 with 3rd party software. In addition, users can control the BioStar 2 platform remotely with the mobile app for BioStar 2 and manage Suprema Mobile Access, a mobile credential system that uses smartphones as access keys.



BioStar 2 TA

Build a more flexible time & attendance system with BioStar 2 TA module. It lets you set an unlimited number of schedules and specify the number of users for each schedule. BioStar 2 time & attendance module is ideal for an enterprise level system or create a variety of time & attendance rules.



Various Shift
Settings



Flexible Work
Management



Easy Shift Type
Setting



Timesheet
Calendar View

BioStar 2 AC

With the purchase of BioStar 2 AC license, you can use advanced access control features like elevator control, advanced anti-passback zone control, fire alarm zone, scheduled lock/unlock zone, intrusion alarm zone, server matching, and video log features.



Customized
System
Architecture



Elevator
Control



Improved Zone
Management




Server
Matching



Video
Logs




Visitor
Management



BioStar 2, certified for data protection

Suprema BioStar 2 platform and access control devices are certified by ISO for data protection measures and are GDPR and CCPA compliant, meeting all of 26 data protection management standards, 114 data protection control and 18 personal information management requirements.

All personal information stored in Suprema products, including biometric data, are encrypted using AES algorithm and the encryption keys are safely managed in cryptochips(SecureElement), with access routes securely blocked.





| Biometrics

Leading provider of biometric solutions since 2000, Suprema has continuously innovated fingerprint and face recognition technology as well as deep learning artificial intelligence that is core to biometric solutions.

Artificial Intelligence

Artificial intelligence is core to biometric recognition technology. Leading provider of biometrics solutions for twenty years, Suprema has naturally advanced its computer vision with machine learning technology as well. Facing and solving real-world problems over the two decades, Suprema has accumulated technological know-how that late comers into the field have not acquired. Because Suprema designs, develops and manufactures the entire product—from algorithm and software to hardware as well—the company possesses technological capability that can optimize and expand upon AI for platforms ranging from the cloud to embedded systems.



Face Recognition



Lately, face recognition products based on visual deep learning technology are pouring into the market. Suprema has developed a unique “Fusion Matching” technology that combines its ten years of experience in IR face recognition with visual face recognition methods. For Fusion Matching, IR and visual cameras each capture face photos, generating two types of templates. Face recognition terminal performs the matching of both IR and visual templates and optimizes the two matching scores, balancing them alongside environmental factors like intensity of illumination. Suprema employs its unique algorithm to fuse the two two scores, yielding a highly accurate recognition performance. FaceStation F2, Suprema’s latest face recognition terminal that utilizes Fusion Matching, boasts false acceptance rate of 1 in 10 billion, matching up to 10,000 people per second.

Fusion matching technology provides enhanced anti-spoofing performance as well. Using both the IR and visual face recognition to check captured images for intensity of illumination and other environmental values, Fusion matching detects various types of fake facial representations.

Fingerprint Recognition

Suprema’s fingerprint recognition technology is the world’s fastest, most accurate and stable with the false acceptance rate of only rate of 1 in 10 million, matching up to 150,000 people per second. Suprema employs a unique sensor imaging technology that reduces image distortion and uniformly corrects the contrast to enhance authentication performance. Suprema technology identifies fake fingerprints forged with various materials like paper, film, rubber, clay, silicone, and adhesives by comparing irregular fingerprint patterns as well as fingerprint images obtained via infrared and white light. Suprema fingerprint recognition received international certifications (NIST MINEX, FBI, IQS, STQC, FVC) and is suitable for governmental and official authentication purposes.





| Mobile

Along with biometrics, using smartphones as credentials is a growing trend in the access control industry. Suprema lets users replace RF cards and fobs with Mobile Access cards and QR codes issued and managed either on Suprema system or 3rd party solutions.



Suprema Mobile Access

Suprema Mobile Access significantly improves user convenience by letting people use smartphones as access cards. Mobile access cards can be issued on either BioStar 2 or Suprema Airfob Portal and users can receive them via email. Suprema Mobile Access can easily be integrated with 3rd party systems.




Suprema Airfob Patch

Suprema Airfob Patch can be attached to existing RF card readers to translate Mobile Access Card's Bluetooth or NFC signals to RF card signal, making them compatible with credentials stored in mobile devices. Airfob Patch works without battery, harvesting energy from RF signals transmitted from the card reader.



QR Code

Suprema offers the option of using QR codes as credential. Suprema's versatile intelligent terminal X-Station 2 can read QR codes composed of up to 32 ASCII codes. QR codes can be issued on BioStar 2 or 3rd party systems.



RFID Reader

Suprema offers card readers that support dual-frequency RFID technology, compatible with a wide range of card types including MIFARE, DESFire, FeliCa and EM. Suprema card readers can also read mobile credentials using both NFC and BLE communication. Recently released Suprema X-Station 2 is equipped with color LCD touchscreen and QR code recognition and can be used to manage time and attendance as well as visitor passage and access control at unmanned facilities.



X-Station 2 | Versatile Intelligent Terminal

- Compatible with most RFID cards, Mobile Access cards, QR codes
- Enhanced security with Secure Boot and OSDP(Open Supervised Device Protocol)
- Built-in Camera for image logs



XPass 2 | Outdoor Compact RFID Device

- Compatible with most RFID cards and dual-frequency
- Mobile Access cards
- IP67 and IK08 Vandal-proof structure



XPass D2 | Outdoor Compact RFID Reader

- Compatible with most RFID cards and dual-frequency
- Mobile Access cards*
- IP67 and IK08 Vandal-proof structure
- SIA OSDP verified

* Suprema Mobile Access is supported on XPass D2 - V02A H/W versions only.

Controller

Suprema controller provides the advantages of a biometric-enabled security over a centralized access control system.



CoreStation | Intelligent Biometric Controller

Designed to accommodate enterprise-level systems, Suprema CoreStation stores up to 500,000 users with an incredible fingerprint matching speed of up to 400,000 match per second. Its multi-port interface also supports nonbiometric access control system such as RFID card readers, door locks, alarms sensors and RTE. With its high-performance, biometric readiness and Ethernet communication, CoreStation lets users access the full features of the BioStar 2 platform. Suprema CoreStation can be used in conjunction with door modules and output extension modules to control up to 132 access points. Suprema modules provides secure connection with encrypted communication.



Output Module (OM-120)

- Up to 12 output relays
- Elevator control with BioStar 2
- Anti-passback, fire alarm feature



Secure Module (SIO2)

- Secure door control
- Encrypted communication
- Compact form factor



Door Module (DM-20)

- Up to 4 doors
- Encrypted communication
- Two Wiegand interfaces



Contactless Solution

Suprema contactless temperature detection solution is a one-stop access control and safety solution that provides both facial recognition and skin temperature detection. Thermal camera measures skin temperature without physical contact while face recognition cameras recognizes registered users to grant or deny access. The solution can recognize people who are wearing masks, and give alerts or block access of those not wearing masks.

Enhanced Security and Safety

- Detects skin temperature and displays on GUI
- Raises alerts or denies access when higher than threshold temperature is detected



Accurate Temperature Measurement

- Increased accuracy of the temperature measurement by pinpointing upper area of the face using Suprema's face recognition algorithm



Contactless and Remote features

- Remote user enrollment via photo uploads
- Detection of users not wearing masks
- Face recognition of users wearing masks



Disclaimer: Suprema products are not used to diagnose any medical conditions. Suprema thermal cameras can identify individuals with skin temperature higher than a preset figure but should not be solely or primarily relied upon to diagnose or exclude a diagnosis of COVID-19, or any other disease. Only a licensed medical professional can determine if a person with elevated skin temperature is symptomatic of a specific medical condition.

System Topology



Depending on customer needs, Suprema access control devices can be set up in a distributed or centralized system.






Distributed System

In distributed systems, IP terminals and readers perform the roles of a controller and reader simultaneously, letting you undertake functions such as user management, access control management, and biometric recognition on a single terminal. Suprema's IP terminals and readers improve system reliability with easy system configuration and distributed management. It also provides the benefits of simple wiring, low installation and maintenance costs.



Centralized System

With Suprema's CoreStation and readers, you can build a centralized system, which is a system based on access control units (ACU). Suprema's centralized system provides enhanced security and excellent system scalability. The centralized system also enables you to upgrade your existing systems at lower installation cost. Integrated with BioStar 2, this system safely stores all information about each user including the user's name, ID, PIN, access rights and fingerprint data on a single device.





CoreStation 4 Door Access Control Kit | Complete Access Control Solution

CoreStation 4 Door Access Control Kit contains all components necessary to secure 4 doors. It includes BioStar 2 Access Control Software, CoreStation door controller, 4x access readers of your choice (RFID or Biometrics), and 50 free credits for Suprema Mobile Access. Easily set up a centralized access control system, choosing the credentials of your choice with options: Card, PIN, biometrics, and mobile access cards.



All-In-One Kit



Cost-Effective



Easy to Install






Development Tools


Suprema G-SDK

Suprema G-SDK is a highly-scalable development kit that enables device management for multi-site, multi-tenant customers. It is mobile and cloud-friendly, allowing you to easily add and manage devices via Device Gateways when a new site is added. Based on gRPC, Suprema G-SDK supports many programming languages including Java, C#, Python, Node.js, Go, and C++.




Suprema Versatile Platform (SVP) Android SDK

The Suprema Versatile Platform(SVP) Android SDK allows you to create customized apps to run on Suprema's time & attendance and workforce management terminals, NOVUS and OMNIS. The SDK is made up of APIs that let you develop Android applications for utilizing NOVUS and OMNIS' full functionality.



BioStar 2 Device SDK

BioStar 2 Device SDK is a development tool that enables you to control the core features of Suprema's terminal through 3rd party software.



BioStar 2 API

BioStar 2 API is a Web API that enables integration between BioStar 2 and 3rd party softwares. BioStar 2 API are standardized and allows communication using REST and JSON, making integration and app development easy.














Product Data sheet


| Product | |  |  |  |  |  |
|--|-----------------------------|--|--|---|---|---|
| Product Name | | FaceStation F2 | FaceStation 2 | FaceLite | BioStation A2 | BioStation 2 |
| General | Biometrics | FSF2-DB, AB: Face / FSF2-ODB: Face, Fingerprint | Face | Face | Fingerprint | Fingerprint |
| | LFD (Live Finger Detection) | FSF2-DB, AB: - / FSF2-ODB: Supported (SW-based) | - | - | Supported | - |
| | Protection Class | IP65 | - | - | - | IP65 |
| | RF Options | FSF2-DB: 125kHz EM & 13.56MHz MIFARE, MIFARE Plus, DESFire EV1/EV2 ²⁾ , FeliCa | FL-DB 125kHz EM & 13.56MHz MIFARE, MIFARE Plus, DESFire EV1/EV2 ²⁾ , FeliCa | FL-DB: 125kHz EM & 13.56MHz MIFARE, MIFARE Plus, DESFire EV1/EV2 ²⁾ , FeliCa | BSA2-OEPW: 125kHz EM | BS2-OEPW: 125kHz EM |
| | | FSF2-AB: 125kHz EM, HID Prox & 13.56MHz MIFARE, MIFARE Plus, DESFire EV1/EV2 ²⁾ , FeliCa, iCLASS SE/SR/Seos | FS2-AWB: 125kHz EM, MIFARE Plus, HID Prox & 13.56MHz MIFARE, DESFire EV1/EV2 ²⁾ , FeliCa, iCLASS SE/SR/Seos | | BSA2-OHPW: 125kHz HID Prox | BS2-OHPW: 125kHz HID Prox |
| | | FSF2-ODB: 125kHz EM & 13.56MHz MIFARE, MIFARE Plus, DESFire EV1/EV2 ²⁾ , FeliCa | | | BSA2-OIPW: 13.56MHz iCLASS SE/SR/Seos | BS2-OIPW: 13.56MHz iCLASS SE/SR/Seos |
| | Mobile | NFC, BLE | FS2-D: NFC / FS2-AWB: NFC, BLE | NFC, BLE | BSA2-OMPW: 13.56MHz MIFARE, MIFARE Plus, DESFire EV1/EV2 ²⁾ , FeliCa | BS2-OMPW: 13.56MHz MIFARE, MIFARE Plus, DESFire EV1/EV2 ²⁾ , FeliCa |
| BSA2-OMPW: NFC / BSA2-OIPW: NFC BSA2-OEPW, BSA2-OHPW: Not Supported | | | | | BS2-OMPW: NFC / BS2-OIPW: NFC BS2-OEPW, BS2-OHPW: Not Supported | |
| Capacity | Max. User ⁽¹⁾ | 100,000 | 30,000 | Face: 30,000 | 500,000 | 500,000 |
| | Max. Credential (1:N) | Face: 50,000 Fingerprint: 100,000 | Face: 4,000 | Face: 4,000 | Fingerprint: 100,000 | Fingerprint: 200,000 |
| | Max. Credential (1:1) | Face: 100,000 Fingerprint: 100,000 PIN: 100,000 Card: 100,000 | Face: 30,000 Card: 30,000 | Face: 30,000 Card: 30,000 | Fingerprint: 500,000 Card: 500,000 PIN: 500,000 | Fingerprint: 500,000 PIN: 500,000 Card: 500,000 |
| | Max. Text Logs | 5,000,000 | 5,000,000 | 5,000,000 | 5,000,000 | 3,000,000 |
| | Max. Image Logs | 50,000 | 50,000 | - | 50,000 | - |
| | | | | | | |
| Interfaces | Wi-Fi | - | FS2-D: Not Supported / FS2-AWB: Supported | - | Supported (Built-in) | Supported (Built-in) |
| | TCP/IP | Supported | Supported | Supported | Supported | Supported |
| | RS-485 | 1ch Host or Slave (Selectable) | 1ch Host or 1ch Slave | 1ch Host or 1ch Slave | 1ch Host or Slave | 1ch Host or Slave |
| | Wiegand | 1ch Input or Output (Selectable) | 1ch In and 1ch Out | 1ch In and 1ch Out | 1ch In and 1ch Out | 1ch In and 1ch Out |
| | I/O | 2ch Inputs | 2 Inputs | 2 Inputs | 2 Inputs | 2 Inputs or 2 Outputs |
| | Relay | 1 Relay | 1 Relay | 1 Relay | 2 Relays | 1 Relay |
| | USB | USB 2.0 (Host) | USB 2.0 (Host) | USB 2.0 (Host) | USB 2.0 (Host) | USB 2.0 (Host) |
| Hardware | CPU | 1.8 GHz Dual Core + 1.4 GHz Quad Core | 1.4 GHz Quad Core | 1.2 GHz Quad Core | 1 GHz Quad Core | 1.0 GHz |
| | Memory | 16 GB Flash + 2 GB RAM | 8 GB Flash + 1 GB RAM | 8 GB Flash + 1 GB RAM | 8 GB Flash + 1 GB RAM | 8 GB Flash + 256 MB RAM |
| | Crypto Chip | Supported | Supported | Supported | Supported | Supported |
| | Audio | 16 bit | 24 bit/Voice DSP (echo cancellation) | 24 bit/Voice DSP (echo cancellation) | 24 bit/Voice DSP (echo cancellation) | 16-bit Hi-Fi |
| | Operating Temperature | -20°C ~ 50°C (-4°F ~ 122°F) | -20°C ~ 50°C (-4°F ~ 122°F) | -20°C ~ 50°C (-4°F ~ 122°F) | -20°C ~ 50°C (-4°F ~ 122°F) | -20°C ~ 50°C (-4°F ~ 122°F) |
| | Tamper | Supported | Supported | Supported | Supported | Supported |
| | Power | Voltage: DC 12V ~ DC 24V / Current: Max. 2.5 A | DC 24V | DC 24V | DC 12V | DC 12V |
| | PoE | - | - | - | Supported | Supported |
| | Dimensions (W x H x D mm) | FSF2-DB, AB: 119.8 x 223 x 23.5 FSF2-ODB: 119.8 x 268.4 x 49.7 | 141 x 164 x 125 | 80 x 170 x 76 | 155 x 155 x 40 | 142 x 144 x 45 |
| | Certifications | CE, FCC, KC, RoHS, REACH, WEEE | CE, FCC, KC, RoHS, REACH, WEEE, BT SIG | CE, FCC, KC, RoHS, REACH, WEEE, BT SIG | CE, FCC, KC, RoHS, REACH, WEEE | CE, FCC, KC, RoHS, REACH, WEEE |

⁽¹⁾ The number of users registered without any credential data. ⁽²⁾ DESFire EV2 cards are supported by having backward compatibility of DESFire EV1 cards. CSN and smart card functions are compatible with Suprema devices.

|  |  |  |  |  |  |  |
|---|--|---|---|--|---|---|
| BioStation L2 | BioLite N2 | BioEntry W2 ⁽³⁾ | BioEntry P2 | X-Station 2 | XPass 2 | XPass S2 |
| Fingerprint | Fingerprint | Fingerprint | Fingerprint | XS2-ODPB, XS2-OAPB: Fingerprint ⁽⁴⁾ | - | - |
| Supported | - | Supported | - | - | - | - |
| - | IP65, IP67 | IP67, IK09 | - | IP65 | IP65, IP67, IK08 | IP65 |
| BSL2-OE: 125kHz EM | BLN2-ODB: 125kHz EM & 13.56MHz MIFARE, MIFARE Plus, DESFire EV1/EV2 ⁽²⁾ , FeliCa | BEW2-ODPB: 125kHz EM & 13.56MHz MIFARE, MIFARE Plus, DESFire EV1/EV2 ⁽²⁾ , FeliCa | BEP2-OD: 125kHz EM & 13.56MHz MIFARE, MIFARE Plus, DESFire EV1/EV2 ⁽²⁾ , FeliCa | XS2-ODPB, XS2-OAPB, XS2-DPB, XS2-QDPB: 125 kHz EM & 13.65 MHz MIFARE, MIFARE Plus, DESFire EV1/EV2 ⁽²⁾ (CSN), FeliCa | 125kHz EM & 13.56MHz MIFARE, MIFARE Plus, DESFire EV1/EV2 ⁽²⁾ , FeliCa | 13.56MHz MIFARE, MIFARE Plus, DESFire EV1/EV2 ⁽²⁾ (CSN), FeliCa |
| | BLN2-OAB: 125kHz EM, HID Prox & 13.56MHz MIFARE, MIFARE Plus, DESFire EV1/EV2 ⁽²⁾ , FeliCa, iCLASS SE/SR/Seos | BEW2-OHPB: 125kHz EM, HID Prox & 13.56MHz MIFARE, MIFARE Plus, DESFire EV1/EV2 ⁽²⁾ , FeliCa | | | | |
| BSL2-OM: 13.56MHz MIFARE, MIFARE Plus, DESFire EV1/EV2 ⁽²⁾ , FeliCa | BLN2-PAB: 125kHz EM, HID Prox & 13.56MHz MIFARE, MIFARE Plus, DESFire EV1/EV2 ⁽²⁾ , FeliCa, iCLASS SE/SR, iCLASS Seos | BEW2-OAPB: 125kHz EM, MIFARE Plus, HID Prox & 13.56MHz MIFARE, DESFire EV1/EV2 ⁽²⁾ , FeliCa, iCLASS SE/SR/Seos | BEP2-OA: MIFARE Plus, DESFire EV1/EV2 ⁽²⁾ , 125kHz EM, HID Prox & 13.56MHz MIFARE, FeliCa, iCLASS SE/SR/Seos | XS2-APB, XS2-QAPB: 125 kHz EM HID Prox & 13.65 MHz MIFARE, MIFARE Plus, DESFire EV1/EV2 ⁽²⁾ , FeliCa, iCLASS SE/SR/Seos | | |
| BSL2-OM: NFC BSL2-OE: Not Supported | NFC, BLE | NFC, BLE | NFC | NFC, BLE | NFC, BLE | Not Supported |
| 500,000 | 10,000 | 500,000 | 10,000 | 500,000 | 200,000 | 50,000 |
| Fingerprint: 100,000 | Fingerprint: 10,000 | Fingerprint: 100,000 | Fingerprint: 10,000 | Fingerprint: 100,000 (XS2-ODPB, XS2-OAPB only) | - | - |
| Fingerprint: 500,000 Card: 500,000 | Fingerprint: 10,000 Card: 10,000 | Fingerprint: 500,000 Card: 500,000 | Fingerprint: 10,000 Card: 10,000 | Fingerprint: 500,000 (XS2-ODPB, XS2-OAPB only) Card: 500,000 PIN: 500,000 | Card: 200,000 PIN: 200,000 | Card: 50,000 |
| 1,000,000 | 1,000,000 | 1,000,000 | 1,000,000 | 5,000,000 | 1,000,000 | 100,000 |
| - | - | - | - | 50,000 | - | - |
| - | - | - | - | - | - | - |
| Supported | Supported | Supported | Supported | Supported | Supported | Supported |
| 1ch Host or Slave | 1ch Host or Slave | 1ch Host or Slave | 1ch Host or Slave | 1ch Host or Slave | 1ch Host or Slave | 1ch Host or Slave |
| 1ch In or Out | 1ch In or Out | 1ch In or Out | 1ch In or Out | 1ch In or Out | 1ch In or Out | 1ch In or Out |
| 2 Inputs | 2 Inputs | 2 Inputs | 2 Inputs | 2 Inputs | 2 Inputs | 2 Inputs |
| 1 Relay | 1 Relay | 1 Relay | 1 Relay | 1 Relay | 1 Relay | 1 Relay |
| - | - | - | - | USB 2.0 (Host) | - | - |
| 1.2 GHz Quad Core | 1.2 GHz | 1.2 GHz Quad Core | 1.0 GHz | 1.5 GHz Quad Core | 1.0 GHz | 533 MHz DSP |
| 2 GB Flash + 256 MB RAM | 4 GB Flash + 64MB RAM | 2 GB Flash + 256 MB RAM | 8 GB Flash + 64 MB RAM | 16 GB Flash + 1 GB RAM | 4 GB Flash + 64 MB RAM | 16 MB Flash + 16 MB RAM |
| Supported | Supported | Supported | Supported | Supported | Supported | Supported |
| 16-bit Hi-Fi | 16-bit Hi-Fi | Multi-tone Buzzer | Multi-tone Buzzer | 24bit | Multi-tone Buzzer | Multi-tone Buzzer |
| -20°C ~ 50°C (-4°F ~ 122°F) | BLN2-ODB, BLN2-OAB: -20°C ~ 50°C (-4°F ~ 122°F) BLN2-PAB: -10°C ~ 50°C (14°F ~ 122°F) | -20°C ~ 50°C (-4°F ~ 122°F) | -20°C ~ 50°C (-4°F ~ 122°F) | -20°C ~ 50°C (-4°F ~ 122°F) | -35°C ~ 65°C (-31°F ~ 149°F) | -35°C ~ 65°C (-31°F ~ 149°F) |
| Supported | Supported | Supported | Supported | Supported | Supported | Supported |
| DC 12V | DC 12V | DC 12V | DC 12V | DC 12V (MAX. 0.8A) or DC 24V (MAX. 0.45A) | DC 12V / DC 24V | DC 12V |
| - | - | Supported | - | Supported | Supported | - |
| 71 x 201 x 44 | 58 x 190 x 44 | 50 x 172 x 43.5 | 50 x 164 x 37.5 | XS2-ODPB/XS2-OAPB: 82 x 208.5 x 25.9 XS2-DPB/XS2-APB: 82 x 159 x 25.9 XS2-QDPB/XS2-QAPB: 82 x 203 x 33.9 | XP2-MDPB: 48 x 145 x 27 XP2-GDPB/GKDPB: 80 x 130 x 25 | 80 x 120 x 11.4 |
| CE, FCC, KC, RoHS, REACH, WEEE | CE, FCC, KC, RoHS, REACH, WEEE | CE, FCC, KC, RoHS, REACH, WEEE, UL 294 | CE, FCC, KC, RoHS, REACH, WEEE | CE, FCC, KC, RoHS, REACH, WEEE | CE, FCC, KC, RoHS, REACH, WEEE, SIG | CE, FCC, KC, RoHS, REACH, WEEE |

⁽³⁾ Some models(BEW2-ODP, BEW2-OAP, BEW2-OHP) do not support BLE. ⁽⁴⁾ Scheduled to be released in the second half of 2021.



| Product | |  |
|--------------|-------------------------------|---|
| Product Name | | CoreStation (CS40) |
| Capacity | Max. User | 500,000 |
| | Max. Credential (1:N) | Face: 100,000 Fingerprint: 100,000 |
| | Max. Credential (1:1) | Face: 500,000 Fingerprint: 500,000 Card 500,000 PIN: 500,000 |
| | Max. Text Logs | 5,000,000 |
| Interfaces | TCP/IP | Supported |
| | RS-485 | 5ch |
| | RS-485 Communication Protocol | OSDP V2 Compliant |
| | Wiegand | 4ch |
| | Relay | 4 Relay |
| | TTL Input | 8ch (Supervised Input Selectable) |
| | TTL Output | 8ch |
| | AUX Input | 2ch (AC Power Fail, Tamper) |
| Connectivity | Max. Slave Devices (RS-485) | Max. 64 devices (Max. 31 devices per port) |
| | Max. Wiegand Devices | Max. 132 devices (with DM-20) |
| Hardware | CPU | 1.4 GHz Octa Core |
| | Memory | 8 GB Flash + 1 GB RAM |
| | LED | Multi-color |
| | Operating Temperature | 0°C ~ 50°C (32°F ~ 122°F) |
| | Tamper | Optional (ENCR-10) |
| | Power | DC 12V |
| | Dimensions (W x H x D mm) | 150 x 214 x 21 |
| | Certifications | CE, FCC, KC, RoHS, REACH, WEEE, UL294 |

| Product | |  |  |
|----------------|---------------------------|---|---|
| Product Name | | BioEntry R2 | XPass D2 |
| General | Biometrics | Fingerprint | - |
| | Protection Class | - | IP65, IP67, IK08 |
| | RF Options | BER2-OD: 125kHz EM & 13.56MHz MIFARE, MIFARE Plus, DESFire EV1/EV2 ⁽⁵⁾ , FeliCa | XPD2-MDB, XPD2-GDB, XPD2-GKDB: 125kHz EM & 13.56MHz MIFARE, MIFARE Plus, DESFire EV1/EV2 ⁽⁵⁾ , FeliCa, NFC & 2.4GHz BLE |
| | Mobile | BER2-OD: NFC | XPD2-MDB, XPD2-GDB, XPD2-GKDB: NFC, BLE |
| Interfaces | RS-485 | 1ch Slave | 1ch Slave |
| | Wiegand | - | 1ch Out |
| Hardware | CPU | 1.0 GHz Quad Core | 80 MHz |
| | Memory | 32 MB Flash + 32 MB RAM | 512 KB Flash + 160 KB RAM |
| | Audio | Multi-tone Buzzer | Multi-tone Buzzer |
| | Operating Temperature | -20°C ~ 50°C (-4°F ~ 122°F) | -35°C ~ 65°C (-31°F ~ 149°F) |
| | Tamper | Supported | Supported |
| | Power | DC 12V | DC 12V |
| | Dimensions (W x H x D mm) | 50 x 164 x 37.5 | XPD2-MDB: 48 x 144.7 x 27 XPD2-GDB/GKDB: 80 x 130 x 25 |
| Certifications | | CE, FCC, KC, RoHS, REACH, WEEE | CE, FCC, KC, RoHS, REACH, WEEE, SIG |

| Product | |  |  |  |
|--------------|---------------------------|---|---|---|
| Product Name | | Output Module (OM-120) | Door Module (DM-20) | Secure Module (Secure I/O 2) |
| Interfaces | RS-485 | 1ch | 1ch | 1ch |
| | Wiegand | - | 2ch | - |
| | Relay | 12 Relays | 4 Relays | 1 Relay |
| | Input | - | TTL Input: 4ch / Supervised Input: 4ch | 2ch |
| | Output | - | 6ch | - |
| | AUX Input | 2ch Dry Contact Input | - | - |
| Hardware | CPU | Cortex M3 72MHz | Cortex M 32MHz | Cortex M 32MHz |
| | Memory | 128 KB Flash + 20 KB SRAM | 128 KB Flash + 20 KB SRAM | 128 KB Flash + 20 KB SRAM |
| | LED | Multi-color | Multi-color | Multi-color |
| | Operating Temperature | -20°C ~ 60°C (-4°F ~ 140°F) | -20°C ~ 60°C (-4°F ~ 140°F) | -20°C ~ 50°C (-4°F ~ 122°F) |
| | Power | DC 12V | DC 12V | DC 12V |
| | Dimensions (W x H x D mm) | 90 x 190 x 21 | 130 x 90.5 x 35.8 | 36 x 65 x 18 |
| | Certifications | CE, FCC, KC, RoHS, REACH, WEEE | CE, FCC, KC, RoHS, REACH, WEEE | CE, FCC, KC, RoHS |

⁽⁵⁾ DESFire EV2 cards are supported by having backward compatibility of DESFire EV1 cards. CSN and smart card functions are compatible with Suprema devices.



Suprema Inc.

17F Parkview Tower, 248, Jeongjail-ro, Bundang- gu, Seongnam-si, Gyeonggi-do, 13554, Republic of Korea

T +82 31 783 4502 www.supremainc.com



For more information visit our website below by scanning the QR code.
<https://www.supremainc.com/en/about/contact-us.asp>

©2021 Suprema Inc. Suprema and identifying product names and numbers herein are registered trade marks of Suprema, Inc. All non-Suprema brands and product names are trademarks or registered trademarks of their respective companies. Product appearance, build status and/or specifications are subject to change without notice. [SUPREMA-AMB-LB-EN-REV29]